

Combination Plate and Cutoff Saw



- ◆ First 36" is Cutoff Saw
- ◆ Allen Bradley PLC Controls
- ◆ Panel View Touch Control Screen
- ◆ Precision Cutting to 0.005"
- ◆ Eliminates Secondary Operations
- ◆ Integral Chip Collection
- ◆ Solid Clamping of Material
- ◆ Easy Saw Blade Change
- ◆ Automatic Load Button
- ◆ Protective Barrier
- ◆ Backgauge Squaring Fence
- ◆ Operator Protective Shields
- ◆ Spring Loaded Clamps
- ◆ Variable Pressure Clamping

MetSaw Systems, Inc

- ◆ 2950 Bay Vista Court ◆ Benicia, CA 94510
- ◆ Tel: 707.746.6200 ◆ Fax: 707.746.5085
- Web site: www.metsaw.com
- E-mail: sales@metsaw.com



Precision

Productivity



Cutoff Section w/Rear Clamp



Allen Bradley PLC



Touch Controls



Easy Blade Change



Chip Collection System



Spring Loaded Clamping

CAPABILITY

Cutting Window:	12 Foot
Cutting Height:	6 Inch
Cutting Length:	1/4" to Unlimited

PRECISION

Straightness of Cut:	+/- 0.005"
Optional Upgrade:	+/- 0.003"
Squareness:	+/- .0005" per 1/2" Thickness
Surface Finish:	Up to 12 micro-inch

FEED RATES

20/30 HP Arbor Motor	2000 RPM
Cutting Speed:	0-500 IPM
Carriage Speed:	1000 IPM
Backgauge Speed:	1000 IPM

POWER REQUIREMENTS

Voltage:	460/480 Three Phase
Air Supply:	30 CFM